



General ordering data

Туре	Order No.
PVC AC 3P+N MCB16 SW SPD1 CG 04	8000135282

Technical data

General data			
Enclosure version	Modular enclosure, 12 modules 1 row		
Mechanical Impact strength:	IK09		
IP Degree protection:	IP65		
Wall thickness	1,5mm		
Mounting plate	Not applicable		
Earth continutiy plate	Not applicable		
Earth stud	Not applicable		
Gland plate specifications	Not applicable		
Label setting	Not applicable		
Document holder	Not applicable		
Fixing lug for wall mounting	Not applicable		
Fixing screws for wall mounting	Not applicable		
Control elements	Not applicable		
Application	400VAC PV enclosure equipped with isolator switch, MCB 16A and SPD type I protection		
Location	Indoor		





No cable glands are mounted. They are supplied as a kit together with the enclosure

Cable entries	
Cable Glands	Supplied as kit [not mounted]: 2x VG M25-1/K68; 1x VG M16 - K 68
Plugs	Not applicable
Compensating elements	Not applicable
Terminal strip	
Horizontal installed	DIN Rail 35x7.5
Power elements	1x SPD: VPU AC I 4 300/12.5 LH 1x MCB 3P 16A C 6kA; 1x AC isolator switch 3P+N 32A 800V
Terminals	1x WDU 6 for neutral connection 1x WPE 10 for earth connection
Cabling	

Fully wired devices inside the enclosure: 4x6mm2 H07Z1-K cable for 4-pole connection and 16mm2 for earth connection

Machining details			
F A		Side A:	
		-	
		Side B:	
		Side C:	
	Side C.		
С	EF	Side D:	
В			
	Side E:		
	Side F:		
Declaration of Conformity			

Low Voltage Directive Standard	Low Voltage Directive IEC EN 61439-1/2/3
Marking	CE